

FLECK® 3150 2-INCH CONTROL VALVE

HIGH PROGRAMMABILITY FOR COMMERCIAL/INDUSTRIAL FILTER AND SOFTENER APPLICATIONS

FEATURE HENEFIT

Lead-free brass valve body for superior strength and durability

Continuous service flow rate of 95 GPM with a backwash of 105 GPM

Backwash capability accommodates softener tanks up to 63" and filter up to 42" in diameter

Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system

Designed for single or multiple tank systems

Environmental protective cover for water resistance, corrosion resistance, and UV stability

Time-tested, hydraulically-balanced

VALVE PECIFICATION

Valve Material Lead-free brass*
Inlet/Outlet 2" NPTF/BSPF

Cycles 3 or 5

FLOW RATE (50 P) INLET) - VALVE ALONE

Continuous 95 GPM (21.6 m³/h)

15 psi drop

Peak 124 GPM (28.2 m³/h)

25 psi drop

Cv 24.8

flow at 1 psi drop

Max. Backwash 105 GPM (23.8 m³/h)

25 psi drop

REGENERATION

Downflow/Upflow Both
Adjustable Cycles Yes

Time Available

Electromechanical: 0 - 164 min/regeneration NXT: 0 - 240 min/cycle XT: 0 - 240 min/cycle

METER INFORMATION

Meter Accuracy

2" Paddle: $3 - 150 \text{ GPM} \pm 5\%$

 $(.68 - 34 \text{ m}^3/\text{h})$

Meter Capacity Range

2" Standard: 1,250 - 21,250 gal

(5 - 75 m³)

2" Extended: 6,250 - 106,250 gal

(24 - 375 m³)

NXT: 1 - 9,900,000 gal

(0 - 37,476 m³



FILTRATION & PROCE

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209

P: 262.238.4400 | WWW.PENTAIRAQUA.COM | CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services. Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.